

FEATURE
<ul style="list-style-type: none">■ Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.■ Innovative, easy installation in minutes.■ Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.■ SALIDA faceplate available.■ Single or double face(Universal)■ Universal J-box mounting pattern.■ 120V-277VAC Dual voltage operation.■ Ultra bright RED or GREEN LEDs.■ Built-in 3.6V1000mAh Ni-MH battery for minimum 90 minutes emergency operation.■ Maximum 24 hours for full recharge time.■ Test switch and charge indicator.■ UL and cULus listed.■ 0° to 40° C indoor damp location listed.

ORDERING INFORMATION		
FAMILY	LENS	HOUSING COLOR
JLECD2	R(RED)	BLANK(WHITE)
	G(GREEN)	B(BLACK)

PACKING INFORMATION		
MODEL NO.	PACKING INFORMATION	WEIGHTS
JLECD2RW	45.5x43x16.5cm/6pcs	6.6/6.0kgs
JLECD2GW	45.5x43x16.5cm/6pcs	6.6/6.0kgs

ELECTRICAL INFORMATION						
MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLECD2RW	120 - 277V	0.032A	3.3W	10Pcs Red LEDs	24 Hrs	90 Mins
JLECD2GW	120 - 277V	0.023A	3.3W	8Pcs Green LEDs	24 Hrs	90 Mins

FAMILY:	JLECD2
NOTES:	
TYPE:	ULTRA THIN EMERGENCY EXIT COMBO

